



Biztonsági armatúra FP 360 sc, SS, szénacél karima készlettel

Termékszám:

LZY630.00.31000

ELAVULT CIKK

Ez a termék már nem elérhető.

Stainless steel ball valve safety armature kit for FP360sc. Including CS flange and piece of pipe. Retractable usage possible when sample is present.

Safe

Safety armature ensures safe installation of the FP360 in a pressurized line.

Robust

Safety armature can be used up to 6 bar.

Easy handling

Probe can be extracted under pressure without stopping the process.

Complete

Welding piece of pipe, flange (both in carbon steel) and gasket are included.

Requirement

Process line, pipe in which the FP360 needs to be installed using this armature, needs to have a minimal diameter of DN100. There is no upper limit for the pipe size. The armature can also be mounted tank walls.

Műszaki adatok

A doboz tartalma:	Stainless Steel safety armature including adapter, CS flange, CS piece of pipe and gasket.
Anyag:	ball valve SS 1.4408 / CF8M or 1.4571 / 316Ti; flange CS C22.8; piece of pipe CS C22.8.
Flange connection:	Use flange (set) to avoid probe damage. LZY616 (in LZY630.00.30000) or LZY617 (in LZY630.00.31000).
Kézikönyv nyelvek:	non-verbal instruction sheet.
Műszer:	All FP 360 sc versions without compressed air cleaning nozzle (LXV441.99.xx1xx and LXV441.99.xx3xx).
Nyomástartomány:	≤ 6 bar / ≤ 87 psi
Súly:	Armature: 18 kg (approximately)

A doboz tartalma

Stainless Steel safety armature including adapter, CS flange, CS piece of pipe and gasket.