



**Be Right™**



## EZ1009 Chromium Cr(VI) Analyser

**Termékszám:**

**EZ1009.XXXXXXXX**

**HUF Ár (nettó):**

**Elérhetőségünk**

### Online colorimetric analysis of dissolved Chromium Cr(VI) in water

EZ1000 Chromium Cr(VI) Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

#### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

#### Flexibility that meets your needs

EZ Series Chromium Cr(VI) Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

#### Műszaki adatok

A doboz tartalma:

EZ1009 Chromium Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour) and 1 x empty 5L Reagent Container with Fittings (for Buffer Solution)

Analóg kimenetek:

Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Anyag:

Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Automatikus tisztítás:

Igen

Demineralised water:

For rinsing / dilution

|                         |  |
|-------------------------|--|
| Detektálási határ:      | $\leq 1 \mu\text{g/L}$   |
| Digitális kimenetek:    | Optional: Modbus (TCP/IP, RS485)   |
| Earth connection:       | Dry and clean earth pole with low impedance ( $< 1 \Omega$ ) using an earth cable of $> 2.5 \text{ mm}^2$        |
| Garancia:               | 24 hónap   |
| Instrument air:         | Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air                               |
| Interferenciák:         | Iron (III), Mercury $> 200 \text{ mg/L}$ , Molybdenum $> 200 \text{ mg/L}$ , Vanadium (V) $> 5 \text{ mg/L}$ .   |
| Kalibrálás:             | Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.                       |
| Környezeti hőmérséklet: | Automatic, 2-point; frequency freely programmable  |
| Lefolyócső:             | 10 - 30 °C $\pm 4$ °C deviation at 5 - 95% relative humidity (non-condensing)                                    |
| Mérés módszer:          | Atmospheric pressure, vented, min. Ø 32 mm   |
| Méréstartomány:         | Colorimetric measurement at 546 nm using diphenylcarbazide method, conform with standard method APHA 3500-Cr (B) |
|                         | 5 - 500 µg/L Cr(VI)  |
|                         | Optional:  |
|                         | 1 - 50 µg/L Cr(VI)   |
|                         | 2 - 125 µg/L Cr(VI)  |
|                         | 2.5 - 250 µg/L Cr(VI)  |
|                         | 0.08 - 2 mg/L Cr(VI) (with internal dilution)  |
|                         | 0.16 - 4 mg/L Cr(VI) (with internal dilution)  |
|                         | 0.5 - 50 mg/L Cr(VI) (with internal dilution)  |
| Méretek (MxSxM):        | 690 mm x 465 mm x 330 mm   |
| Minta hőmérséklet:      | 10 - 30 °C   |
| Minta minőség:          | Maximum particle size 100 µm, $< 0.1 \text{ g/L}$ ; Turbidity $< 50 \text{ NTU}$                                 |
| Minta: nyomás:          | By external overflow vessel  |
| Mintaáram:              | 100 - 300 mL/min   |
| Mintacellák:            | 10 min (dilution + 5 min)  |
| Mintautak száma:        | 1, 2, 4, or 8  |
| Paraméter:              | Chromium Cr(VI), dissolved   |
| Pontosság:              | Better than 2% full scale range for standard test solutions  |
| Reagent Requirements:   | Keep between 10 - 30 °C  |
| Riasztás:               | 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts                            |
| Súly:                   | 25 kg  |
| Szünet mód:             | 100 - 240 VAC, 50/60 Hz  |
| Tanúsítványok:          | CE compliant / ETL certified   |
| Teljesítmény:           | 100 - 240 VAC, 50/60 Hz  |
|                         | Max. power consumption: 120 VA   |
| Típus:                  | EZ1009   |
| Validation:             | Automatic; frequency freely programmable   |
| Védeeltségi osztály:    | Analyser cabinet: IP44 / Panel PC: IP65  |

## A doboz tartalma

EZ1009 Chromium Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour) and 1 x empty 5L Reagent Container with Fittings (for Buffer Solution)