



EZ1022 Hydrogen Peroxide Analyser

Termékszám: EZ1022.XXXXXXXXXX
HUF Ár (nettó): Elérhetőségünk

Online colorimetric analysis of Hydrogen Peroxide (H₂O₂) in water

EZ1000 Hydrogen Peroxide Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Hydrogen Peroxide Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Műszaki adatok

A doboz tartalma:	EZ1022 Hydrogen Peroxide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 2 x empty 2.5L Glass Containers with Fittings (for Colour and Buffer Solution)
Analóg kimenetek:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Anyag:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: galvanised steel, powder coated
Automatikus tisztítás:	Igen
Demineralised water:	For rinsing / dilution

Detektálási határ:	≤ 2 µg/L
Digitális kimenetek:	Optional: Modbus (TCP/IP, RS485)
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²
Garancia:	24 hónap
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferenciák:	Oxidants like Bromine, Bromamine, Chlorine, Copper Cu(II) > 8 mg/L, Chromate, Iodine, Iodoamines, Iron Fe(III) > 20 mg/L, Nitrite, Ozone and Manganese may oxidize the DPD colour solution. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Kalibrálás:	Automatic, 2-point; frequency freely programmable
Környezeti hőmérséklet:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Lefolyócső:	Atmospheric pressure, vented, min. Ø 32 mm
Mérés módszer:	Colorimetric measurement at 510 nm using DPD
Méréstartomány:	5 - 500 µg/L H ₂ O ₂
	Optional:
	2 - 125 µg/L
	2 - 250 µg/L
	0.04 - 2.0 mg/L (with internal dilution)
	0.08 - 4.0 mg/L (with internal dilution)
	0.5 - 50 mg/L (with internal dilution)
Méreték (MxSZxM):	690 mm x 465 mm x 330 mm
Minta hőmérséklet:	10 - 30 °C
Minta minőség:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Minta: nyomás:	By external overflow vessel
Mintaáram:	100 - 300 mL/min
Mintacellák:	10 min (dilution + 5 min.)
Mintautak száma:	1, 2, 4, or 8
Paraméter:	Hydrogen Peroxide
Pontosság:	Better than 2% full scale range for standard test solutions
Reagent Requirements:	Keep refrigerated.
Riasztás:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Súly:	25 kg
Szünet mód:	100 - 240 VAC, 50/60 Hz
Tanúsítványok:	CE compliant / ETL certified
Teljesítmény:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Típus:	EZ1022
Validation:	Automatic; frequency freely programmable
Védettségi osztály:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65

A doboz tartalma

EZ1022 Hydrogn Peroxide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 2 x empty 2.5L Glass Containers with Fittings (for Colour and Buffer Solution)