



EZ4043 Total Hardness Analyser

Termékszám: EZ4043.XXXXXXXXXX
HUF Ár (nettó): Elérhetőségünk

Online, automatic titration of Total Hardness in water monitoring applications

State of the art titration platform

The EZ4000 Series Analysers are single-parameter titrators built on an industrial analytical platform. High precision dispensers, robust peristaltic pumps and carefully designed liquid pathways all add up to the highest performance for industrial and environmental analysis needs.

Unique flexibility in titration methods

Every application starts with the basics: the right titrimetric technique for the parameter of interest, the measuring range and the water matrix. Depending on the change in the specific variables, the EZ4000 Series run either acid-base, redox, precipitation or photolorimetric titration allowing for a unique flexibility.

The EZ4043 Total Hardness Analysers use colorimetric titration and have a standard measuring range of 0.05 - 10 mg/L CaCO₃. They combine an unparalleled expertise in online titration with a set of unique analysis, control and communication features in a compact footprint:

- Smart automatic features
- Control and communication via industrial panel PC
- Analogue and digital output options
- Multiple stream analysis (up to 8 streams)

There are many additional options available. Please contact Hach for more details.

Műszaki adatok

A doboz tartalma:	EZ4043 Total Hardness Analyser, Instruction Manual, 1 x Double Bit Door key, 1 x Mounting Brackets, 3 x empty 5L Reagent Containers with Fittings (for Buffer, Colour & Acid Solution) and 1 x empty 10L Reagent Container with Fittings (for EDTA Solution)
Analóg kimenetek:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Anyag:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Demineralised water:	For rinsing / dilution

Detektálási határ:	≤ 0.25 mg/L
Digitális kimenetek:	Optional: Modbus (TCP/IP, RS485)
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²
Garancia:	24 hónap
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferenciák:	Some metal ions interfere by causing fading or indistinct end points or by stoichiometric consumption of EDTA. Suspended or colloidal organic matter also may interfere with the end point. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Kalibrálás:	N.A.
Környezeti hőmérséklet:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Lefolyócső:	Atmospheric pressure, vented, min. Ø 32 mm
Mérés módszer:	Colorimetric titration by EDTA using colour indicator calmagite at 620 nm
Méréstartomány:	0.25 - 10 mg/L CaCO ₃
	Optional:
	Internal dispenser dilution (max. factor 100)
Méretek (MxSZxM):	690 mm x 465 mm x 330 mm
Minta hőmérséklet:	10 - 30 °C
Minta minőség:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Minta: nyomás:	By external overflow vessel
Mintaáram:	100 - 300 mL/min
Mintacellák:	10 - 15 minutes
Mintautak száma:	1, 2, 4 or 8
Módszer név:	Titrimetric
Paraméter:	Hardness, total
Pontosság:	Better than 2% full scale range for standard test solutions
Reagent Requirements:	Keep between 10 - 30 °C
Riasztás:	1x malfunctioning, 4x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Súly:	25 kg
Tanúsítványok:	CE compliant / UL certified
Teljesítmény:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Típus:	EZ4043
Validation:	Automatic; frequency freely programmable
Védettségi osztály:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65

A doboz tartalma

EZ4043 Total Hardness Analyser, Instruction Manual, 1 x Double Bit Door key, 1 x Mounting Brackets, 3 x empty 5L Reagent Containers with Fittings (for Buffer, Colour & Acid Solution) and 1 x empty 10L Reagent Container with Fittings (for EDTA Solution)