



EZ7621 Total Nitrogen + Total Phosphorus Analyser

Termékszám: EZ7621.XXXXXXXX

HUF Ár (nettó): Elérhetőségünk

The power of the perfect pair: TN and TP

You spend a lot of time looking at your data and your process, so you never come close to any compliance issues while managing your environmental and regulatory goals. When you choose the new EZ Series Total Nitrogen and Total Phosphorus analyser from Hach, you'll get industry-leading technology with the power to measure both parameters in one analyser for an hour-by-hour picture of nutrient removal efficiency. Full process insight gives you the confidence to take action.

Stay in control.

Be confident in your process. Measuring Total Nitrogen and Total Phosphorus can be a complicated array of processes, but you can be in control. Hach's new TN/TP analyser simplifies the process by helping you get both measurements, quickly and accurately, with one device. When you choose our TN/TP analyser, you'll get industry-leading technology and unparalleled Hach service and support. We are your partner in managing your environmental and regulatory goals, and we're here to help you optimise your work.

See the total picture.

Get a complete picture of your nutrient removal process with the reliable data and insights you need to act quickly and with confidence. Total nutrient discharge permits evolve, and with Hach's new EZ Series Total Nitrogen and Total Phosphorus analyser you'll get actionable data every hour. You'll always see the total load of Nitrogen and Phosphorus in your water.

This isn't simple, but we'll help you simplify.

Hach is monitoring wastewater in new and exciting ways. We know that monitoring total nitrogen and total phosphorus can be a complicated process. That's why our new TN/TP analyser gives you the power to simplify your process and get accurate readings. The new combined analyser will make your day easier with features that help you save hands-on time. You'll enjoy the autocalibration, self-cleaning and automatic validation this analyser provides.

Műszaki adatok

A doboz tartalma: EZ7621 Total Nitrogen & Total Phosphate Analyser, Instruction Manual, 1 x Double Bit Door

Key, 1 x Mounting Brackets, 3 x empty 2.5L Reagent Containers with Fittings (HCl, NaOH and H_2SO_4 Solution) and 3 x empty 2.5L Glass Reagent Containers with Fittings (Colour, Reductor &

Persulphate Solution)

Analóg kimenetek: Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Anyag: Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Automatikus tisztítás: Igen

Demineralised water: Consumption: 140 mL/analysis (hour)

Detektálási határ: TN: $\leq 0.1 \text{ mg/L}$

TP: $\leq 0.005 \text{ mg/L}$

Digitális kimenetek: Optional: Modbus (TCP/IP, RS485)

Earth connection: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²

Garancia: 24 hónap

Instrument air: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Interferenciák: TN: The main interferences are Br and I . When the amount of I is 2.2 fold of the amount of

TN, or the amount of Br⁻ is 3.4 fold of the amount of TN, this will interfere on the test results. Dissolved organic matter, surfactants and Chromium (VI) interfere. Various inorganic substances not normally found in natural water, such as Chlorite $[C|O_1]$ and Chlorate $[C|O_2]$, may interfere.

TP: Arsenic (V), Chromium (VI), Copper (II) > 10 mg/L, Iron (III) > 10 mg/L, Sulphide > 2 mg/L, and Vanadium (V), Silica > 60 mg/L. Large amounts of colour and turbidity interfere. Fats, oil,

proteins, surfactants and tar.

Kalibrálás: Automatic, 2-point; frequency freely programmable

Környezeti hőmérséklet: 10 - 30 °C, ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)

Lefolyócső: Atmospheric pressure, vented, min. Ø 32 mm

Mérés módszer: TN: UV photometric measurement at 220 nm after persulphate digestion in alkaline medium,

based on APHA 4500-NO3 (B)

TP: Colorimetric measurement at 700 nm using ascorbic acid reduction and molybdate colour

solution after persulphate digestion in acidic medium, based on APHA 4500-P

Méréstartomány: 0.1 - 2 mg/L TN; 0.005 - 1 mg/L TP

Méretek (MxSZxM): 690 mm x 465 mm x 330 mm

Minta hőmérséklet: 10 - 30 °C

Minta minőség: Maximum particle size 100 μm, < 0.1 g/L; Turbidity < 50 NTU

Minta: nyomás: By external overflow vessel

Mintaáram: 100 - 300 mL/min

Mintacellák: Standard measurement cycle time for both TN & TP: 60 minutes

Mintautak száma: 1, 2, 4, or 8

Paraméter: Total Nitrogen (TN), Total Phosphorus (TP)

Pontosság: Better than 3% (TN) and 2% (TP) full scale range for standard test solutions

Reagent Requirements: Keep between 10 - 30 °C

Riasztás: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Súly: 25 kg

Tanúsítványok: CE compliant / ETL certified

Teljesítmény: 230 VAC, 50/60 Hz

120 VAC, 50/60 Hz

Max. power consumption: 440 VA

Validation: Automatic; frequency freely programmable

Védettségi osztály: Analyser cabinet: IP55 / Panel PC: IP65

A doboz tartalma EZ7621 Total Nitrogen & Total Phosphate Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 3 x empty 2.5L Reagent Containers with Fittings (HCl, NaOH and H₂SO₄ Solution) and 3 x empty 2.5L Glass Reagent Containers with Fittings (Colour, Reductor & Persulphate Solution)