



EZ4004 Total Alkalinity Analyser

Termékszám: EZ4004.XXXXXXXXXX
HUF Ár (nettó): Elérhetőségünk

Online, automatic titration of Alkalinity in water monitoring applications

State of the art titration platform

The EZ4000 Series Analysers are single-parameter titrators built on an industrial analytical platform. High precision dispensers, robust peristaltic pumps and carefully designed liquid pathways all add up to the highest performance for industrial and environmental analysis needs.

Unique flexibility in titration methods

Every application starts with the basics: the right titrimetric technique for the parameter of interest, the measuring range and the water matrix. Depending on the change in the specific variables, the EZ4000 Series run either acid-base, redox, precipitation or photolorimetric titration allowing for a unique flexibility.

The EZ4004 Total Alkalinity Analysers use acid-base titration. They combine an unparalleled expertise in online titration with a set of unique analysis, control and communication features in a compact footprint:

- Wide standard range of 100 - 2500 mg/L CaCO₃
- Smart automatic features
- Control and communication via industrial panel PC
- Analogue and digital output options
- Multiple stream analysis (up to 8 streams)

There are many additional options available. Please contact Hach for more details.

Műszaki adatok

A doboz tartalma:	EZ4004 Alkalinity Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x pH Electrode, Routine S7 Connection, and 1 x empty 10L Reagent Container with Fittings (for HCl Solution)
Analóg kimenetek:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Anyag:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated

Demineralised water:	For rinsing / dilution
Detektálási határ:	≤ 10 mg/L
Digitális kimenetek:	Optional: Modbus (TCP/IP, RS485)
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²
Garancia:	24 hónap
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferenciák:	Soaps, oily matter, suspended solids or precipitates may coat the glass electrode and cause a sluggish response. Allow additional time between titrant additions to let the electrode come to equilibrium or clean the electrodes occasionally.
Kalibrálás:	Automatic, 2-point; frequency freely programmable
Környezeti hőmérséklet:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Lefolyócső:	Atmospheric pressure, vented, min. Ø 32 mm
Mérés módszer:	Acid-base titration with hydrochloric acid
Méréstartomány:	100 - 5000 mg/L CaCO ₃
	Optional:
	10 - 500 mg/L CaCO ₃
	25 - 1250 mg/L CaCO ₃
	50 - 2500 mg/L CaCO ₃
	Internal dispenser dilution (max. factor 100)
Méreték (MxSZxM):	690 mm x 465 mm x 330 mm
Minta hőmérséklet:	10 - 30 °C
Minta minőség:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Minta: nyomás:	By external overflow vessel
Mintaáram:	100 - 300 mL/min
Mintacellák:	10 - 15 minutes
Mintautak száma:	1, 2, 4 or 8
Módszer név:	Titrimetric
Paraméter:	Alkalinity, total
Pontosság:	Better than 2% full scale range for standard test solutions
Reagent Requirements:	Keep between 10 - 30 °C
Riasztás:	1x malfunctioning, 4x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Súly:	25 kg
Tanúsítványok:	CE compliant / UL certified
Teljesítmény:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Validation:	Automatic; frequency freely programmable
Védettségi osztály:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65

A doboz tartalma

EZ4004 Alkalinity Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x pH Electrode, Routine S7 Connection, and 1 x empty 10L Reagent Container with Fittings (for HCl Solution)