



EZ2306 Total Iron + Total Dissolved Iron Fe(II+III)

Termékszám: EZ2306.XXXXXXXXXX
HUF Ár (nettó): Elérhetőségünk

Online colorimetric analysis of Total Iron + Total Dissolved Iron Fe(II+III) in water

EZ2000 Total Iron Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

EZ2000 Total Iron Analysers have an internal digestion unit. This additional step prior to analysis allows to measure non-soluble or complexed metal species.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Total Iron Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Műszaki adatok

A doboz tartalma:	EZ2306 Iron Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 2 x empty 2.5L Reagent Containers with Fittings (for Reductor & Buffer Solution) and 1 x empty Glass Reagent Container with Fittings (for Colour Solution)
Analóg kimenetek:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Anyag:	Hinged part: Thermoform ABS, door: PMMA

Demineralised water:	Wall section: Galvanised steel, powder coated
Detektálási határ:	For rinsing / dilution
Digitális kimenetek:	$\leq 2 \mu\text{g/L}$
Earth connection:	Optional: Modbus (TCP/IP, RS485)
Garancia:	Dry and clean earth pole with low impedance ($< 1 \text{ Ohm}$) using an earth cable of $> 2.5 \text{ mm}^2$
Instrument air:	24 hónap
Interferenciák:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Kalibrálás:	Metal ions like Lead $> 10 \text{ mg/L}$, Zinc $> 2 \text{ mg/L}$, Nickel $> 2 \text{ mg/L}$, Iron $> 5 \text{ mg/L}$, Copper $> 5 \text{ mg/L}$. Strong oxidising agents, Cyanide, Nitrite, Phosphate (polyphosphate more than orthophosphate), Chromium, Zinc in concentrations exceeding 10 times that of Iron. Bismuth, Cadmium, Mercury, Molybdate, and Silver precipitate Phenanthroline. Polyphosphate must be absent. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Környezeti hőmérséklet:	Automatic, 2-point; frequency freely programmable
Lefolyócső:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Mérés módszer:	Atmospheric pressure, vented, min. Ø 32 mm
Méréstartomány:	Colorimetric measurement using TPTZ colour solution, conform with APHA 3500-Fe (B)
	0.01 - 1 mg/L Fe
	Optional:
	0.005 - 0.25 mg/L
	0.005 - 0.5 mg/L
	0.08 - 4 mg/L (with internal dilution)
	0.16 - 10 mg/L (with internal dilution)
Méreték (MxSZxM):	690 mm x 465 mm x 330 mm
Minta hőmérséklet:	10 - 30 °C
Minta minőség:	Maximum particle size 100 μm , $< 0.1 \text{ g/L}$; Turbidity $< 50 \text{ NTU}$
Minta nyomás:	By external overflow vessel
Mintaáram:	100 - 300 mL/min
Mintacellák:	20 min Total Fe (dilution + 5 min)
	30 min Total Fe & Fe (II); Fe (II+III)
	40 min Total Fe & Fe (II+III) & Fe (II) & Fe (III)
Mintautak száma:	1, 2, 4 or 8
Paraméter:	Iron, total; Fe(II+III), total dissolved
Pontosság:	Better than 2% full scale range for standard test solutions
Reagent Requirements:	Keep between 10 - 30 °C
Riasztás:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Súly:	25 kg
Tanúsítványok:	CE compliant / UL certified
Teljesítmény:	230 VAC, 50/60 Hz
	120 VAC, 50/60 Hz
	Max. power consumption: 440 VA
Típus:	EZ2306
Validation:	Automatic; frequency freely programmable

A doboz tartalma

EZ2306 Iron Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 2 x empty 2.5L Reagent Containers with Fittings (for Reductor & Buffer Solution) and 1 x empty Glass Reagent Container with Fittings (for Colour Solution)